

# Universal Slider and Angle Mount Kit (C13)

## Install Instructions



**Read through all of the instructions completely before beginning the install.**

**Parts Included:**

- 4, 5/16" X 18 ¾ bolts
- 8, 5/16" X 18 lock nuts
- 1, Wire
- 2, sliders (slider handle is right side)
- 2, Angle brackets

**Tools needed:**

- Needle nose pliers
- Standar (flat head) screwdriver
- 3/8" socket or wrench

**Remove all parts from the box and unwrap completely using the packaging to lay out the pieces.**

**Time:**

Approx 15 minutes.

1. Remove plastic knobs and discard (these are for shipping purposes only)
2. Place threaded posts in slider facing floor board or into existing mount holes with release handle facing forward. Secure with nuts.
3. When placing black angle brackets on sliders. Face up for more height or down for lower height.

### **Handle Side**

4. To expose the underside of the rear mounting hole, adjust slider all the way back.
5. Line up square holes on bracket with square holes on slider
6. Place bolts through rear square hole on angle bracket into rear square hole on slider. Thread nut onto rear bolt and tighten.
7. Adjust slider all the way forward.
8. Place bolts through front square hole on angle bracket into front square hole on slider. Thread nut onto front bolt and tighten.
9. Adjust slider back to center.

### **Non-Handle Side**

10. Use the screwdriver to open adjusting arm and slide the non-handle side all the way back to expose underside of rear mounting hole.
11. Line up square holes on bracket with square holes on slider.
12. Place bolts through back square hole on angle bracket into back square hole on slider. Thread nut onto rear bolt and tighten.
13. Use the screwdriver to open adjusting arm and slide all the way forward.
14. Place bolts through square hole on angle bracket into square hole on slider. Thread nut onto front bolt and tighten.
15. All nuts and bolts should be used and tightened at this time.
16. Use the screwdriver to open adjusting arm and adjust slider back to center, making sure to line up with the handle side.

### **Adjuster**

17. With pliers, make a loop on one end of the provided wire.
18. Place loop end of the wire through the last hole on the slider adjuster arm.
19. Measure length diagonally to non-handle side of slider.
20. Cut the wire to length leaving enough to loop through second to last hole (closest to opening on adjusting arm)
21. Close wire loop

If you have any questions or experience issues, please contact your retail outlet first for help. However, the staff at PRP Seats is always happy to help at **1-800-317-6253**.

**Thank you! Ride safe!**