

Install Instructions

PRP Seats

Bronco Rear Bench Seat Covers

Seats Installation



Parts

A.



B.



C.



Read through all of the instructions completely before beginning the install.

Parts Included:

A. Seat Covers

- 1 x Driver Top Cover
- 1 x Driver Bottom Cover
- 1 x Passenger Top Cover
- 1 x Passenger Bottom Cover
- 2-3 x Head Rest Covers

Tools Needed: (not included)

- Wide Nose Pliers
- Scissors

Time:

Approx 2 Hours.



1. The installation steps for the Rear Bench Seats are mostly the same between the 2 Door and 4 Door Bronco Models. But there are a few specifics that will come up.

2 Door Broncos - have a 50/50 split bench seats
4 Door Broncos - have a 60/40 split bench

We recommended keeping the rear bench seats in the vehicle to install, since it's a lot of work to remove the entire bench.



2. **Top Cover Installation**

Start by removing the headrests from the seats (either 2 or 3 depending on your model).

Find the correct Driver or Passenger side top cover, and start to place it over the Seat.

On 4 Door Models, the 60-Section of the bench will need to have the cover placed underneath the center seatbelt, before you start placing the cover on.



3. Pull the cover down over the seat, and push the flap on the bottom through the center of the seat.

60-Section - We have included a slot in the cover for the car seat anchor to fit through.

TIP - you can release and partially fold the seat to make it easy to get the cover into place, and access hard to reach spots.



4. On the sides of the seat, push the small flaps behind and around the plastic until they are tight. Then remove the protective fleece, and attach to the back of the PRP cover with the velcro strips.

On the top of the seat, push the cover under the plastic slots for the headrests. Start on one corner, and then work your way around until the cover is flush under the plastic.



5. Once the cover is mostly set in place, go to the back of the seat.

On The 60 Section - Close up the zipper on the back of the seat, then tuck in the excess back under the cover.

Try to get the square cutouts for the carseat anchors lined up as best you can.



6. On the backside of the seat, lift up the OEM flap. Then pull the PRP cover flap through the center. Pull this flap extra hard, and then attach to the top cover with the velcro strips. You may need to readjust the cover, or tighten the velcro as needed.

TIP - Use a pair of wide nose pliers to pull the flap extra tight. It will allow for less movement in the cover, and give the cover a better looking fit overall.



7. **Bottom Cover Installation**

Grab the bottom cover and ensure you have the correct side. Then place it over the seat.

Start by tucking the back of the cover through the center of the seat, and wrapping it around the back first.

Then pull the cover over the front of the seat, and pull it down until its seated correctly.

TIP - Partially fold down the seat to make this easier.



8. Pull down on all the sides and corners of the cover, until its tight all around.

Then feed the drawstring inbetween the plastic brackets and the seat, on both sides.

Take one end of the drawstring, and feed it though the ribbon loops on the back of our cover.



9. Pull the drawstrings together. You can use pliers to pull them extra tight, and hold it in place while you tie them off. After it's tied off, and you are happy with the fitment of the cover, cut off any excess string.

NOTE - Try to get the drawstring as tight as you can. It will allow for less movement in the cover, and give the cover a better looking fit overall.



10. Headrest Cover Install

Place the cover on top of the headrest (the Rubber PRP label should go on the back of the headrest).

4 Door Bronco's - also have an additional center headrest. Make sure the large headrest covers have the release button on the correct side. Then push the cover under the plastic of the button, until it is flush.



Pull the cover down and over the headrest - use your fingers to depress the foam on the sides to make this easier. Then attach the velcro strips to get it tight. Readjust the cover as needed until the logo is centered.

Then place the headrests back on the seats.



11. ... And You're All Done!

If you have any questions or experience issues, please contact your retail outlet first for help. However, the staff at PRP Seats is always happy to assist you.

1-800-317-6253.
customerservice@prpseats.com
Thank you! Ride safe!