Install Instructions

PRP Seats
Can-Am Maverick Trail Sport 2
Seat /4 Seat
Net Installation

Parts

A.

B.

Read through all of the instructions completely before beginning the install.

Parts Included:
A. Window Nets (Either 2 or 4)
B. Hardware
        2 x 3/8" bolt with nut

Remove all parts from the box and unwrap completely using the packaging to lay out the pieces.

Tools Needed: (not included)
3/8 Socket

Time:
Approx 30-45Minss.

PRP

1. Start by attaching Top-Rear of the net to the cage. Use our supplied Bolt and Nut to attach the strap to the bolt holes on the cage. This strap has a plastic clip included - When you want to get in/out, you can undo this clip and open the door

2. Attach the Bottom of the net to the door. There are two straps on the bottom of the net. Line these up with the corresponding torx bolts located on the door. Remove those bolts, place the strap over the hole, and reinstall the torx bolts so that they now hold that strap in place.

3. Attach the Hook'n Loop strips in the front. These loops have two pieces – an adhesive loop that permanently attaches and stays fixed to the cage, and another cut loop that is attached to the net.

a. Attach the bottom corner loop first. Pull the net into the corner until it is tight to get the placement. Then remove the paper film and attach the adhesive so that the loop wraps around the bar. Once that is done, wrap the second loop onto the first, so the window net stays tight.

b. Attach the upper corner loop. Pull the net into the corner until it is tight to get the placement. Then remove the paper film and attach the adhesive so that the loop wraps around the bar. Once that is done, wrap the second loop onto the first, so the window net stays tight.

4. And you're all set!

If you have any questions or experience issues, please contact your retail outlet first for assistance. However, the staff at PRP is always happy to help at 1-800-317-6253, or email customerservice@prpseats.com

Thank you! Ride Safe!

PRP