

Install Instructions

PRP Seats

Bronco Rear Bench Seat Covers

Seats Installation



A.



B.



C.



Read through all of the instructions completely before beginning the install.

Parts Included:

A. Seat Covers

- 1 x Driver Top Cover
- 1 x Driver Bottom Cover
- 1 x Passenger Top Cover
- 1 x Passenger Bottom Cover
- 3 x Head Rest Covers

Tools Needed: (not included)

- Wide Nose Pliers/ Channel Locks
- #3 Phillips Screwdriver
- Scissors

Time:

Approx 2 Hours.



1. Remove Bottom Cushion

Start by removing the bottom seat cushion. There are two retention latches underneath the driver and passenger sides. Place your hands under the front of the seat, and pull up hard until those clips unlatch. Then pull the cushion up and remove it from the vehicle.

Note: On certain models you will need to unplug the occupancy sensors or seat heaters before you remove the cushion.



2. Unlatch Rear Carpet Panels

Next go into the trunk, and find the carpet panels directly behind the seat backs. Pull up on these carpet panels to unlatch/pop off the various green push pins until both panels are free.

You will now be able to easily access underneath the seat.



3. Remove Headrests

Remove all three headrests. Press the button, and pull up to remove each headrest. You may need to fold the bench forward slightly to get the headrest completely off.

WARNING: Be careful not to step on or damage the wires on the floor while installing the covers.



4. Remove the Center Armrest

Start by folding down the Driver Side Bench. You will now see a plastic hinge cover on the side of the armrest. Pop this over off by pulling it upwards and forward.



5. Remove the Center Armrest (Cont.)

With the cover off you will now see a phillips head hinge bolt. Use a **#3 Phillips Head Screwdriver** to remove this bolt and set it aside. If the bolt is too tight to loosen by hand, you can attach vise grips to the screwdriver to gain more force to break the bolt loose.

WARNING: This bolt was easy to strip with the force required to remove it. So make sure to use a #3 screwdriver to prevent damage.

6. Remove the Center Armrest (Cont.)

With the bolt removed, pull the armrest forward slightly, then angle it upwards (towards the passenger window) until the bracket unlatches from the seat.

7. (2021+ Outback) Remove Shoulder Seat Belt Guide

Use a #3 Phillips Head Screwdriver to remove the 2x bolts. Then pop off the plastic cover and set it aside.

8. Install the Passenger Side Top Cover

Grab the larger top cover, and make sure the zippers are open. Angle the seat forward slightly by pressing the release button on the seat shoulder.

Then slide the cover over the top of the seat and pull it down. Work the cover back and forth until it fits correctly on the seat. Ensure the square cutout for the release handle is lined up correctly on the shoulder.

9. Tuck the Cover Under the Headrest Slots

The top of the seat has multiple cutout holes for the headrests. Pull the cutout hole to one side, and tuck the hole under one corner of the plastic for the headrest slot. Then work your way around and tuck the rest of the cover hole under the plastic so it sits flush underneath.



10. Close the Zipper on the Back

Close the zipper on the back side. Tuck the excess zipper back and up underneath the cover.

Make sure the square cutouts on the back line up with the child anchor points so that they are accessible.



11. Push the Front Flap through the Center of the Seat

Then lower the seat down, go to the back of the seat, and pull that front flap through.



12. Unclip the Stock Seat Flap, and Replace with the PRP Cover Flap

On the back of the seat you will find the OEM top and bottom covers attached to one another with a Arrow Clip.

Separate/Undo that clip by grabbing it from the side and pulling. Then tuck the OEM bottom flap down and out of the way.



13. Attach the PRP Flap to the OEM Clip

Take the PRP Bottom Flap and insert it into the OEM Top Flap. Just push that arrow clip in on one side, then click it in across the clip.

Then just check the cover fitment, push and pull the material around and adjust as needed for the best fitment for the cover.



14. Install Center Console Cover

Take your center console, and slide the PRP cover over the front of it. Make sure the cutout for the cupholders is on the correct side.



15. Install Center Console Cover (Cont.)

Close up the zipper on the back. Then take the excess zipper on both sides and tuck it in and behind the cover to hide it.



16. Tuck the Cover Under the Cupholders

Start at one corner and push the material under the plastic of the cupholder. Then continue around the sides until all the material is sitting flush underneath the plastic.



17. Re-Install the Armrest

Put the armrest back onto the bench the same way you took it off. There is a keyhole style rod that you need to line up before you insert it back in. Angle the armrest and insert it.

Once the armrest is in, line up the bolt hole on the outside with the support bracket.



18. Re-Install Phillips Bolt

Use a **#3 Phillips Head Screwdriver** to re-install the OEM bolt. Ensure that it is tight.



19. Re-Install Plastic Covers

Angle the plastic cover so that its straight up, push it in so that the cover lines up with the bolt head, then rotate the cover back/down so that the clip on the back of the cover slides over the metal bracket.

(2021+ Outback) - Place the plastic Shoulder Seat Belt Guide back on, and re-install the 2x bolts with a #3 Screwdriver.



20. Install Driver Side Top Cover

Place the cover over the seat and slide it down. Tuck in the material on the side next to the door as needed. Push the bottom flap through the center of the seat.



21. Tuck the Cover Under the Headrest Slots

Make sure the cutout holes for the headrests are lined up. Pull the cutout hole to one side, and tuck the hole under one corner of the plastic for the headrest slot. Then work your way around and tuck the rest of the cover hole under the plastic so it sits flush underneath.



22. Close the Zipper on the Back Side

Once the zipper is closed, tuck the excess zipper underneath the cover to hide it.



23. Attach the Cover Back Flap

Just like on the passenger side, detach the OEM top and bottom flaps, then connect the PRP bottom flap to the OEM top flap.



24. Re-Install Rear Carpet Panels

Place the carpet panels back down, and line up the various clips with the holes on the floor of the trunk. Press all the clips back in until both carpet panels are secured.



25. Install Bottom Cushion

Place the bottom cushion onto a clean workbench.

Ensure that the PRP Cover has 4x Separate draw strings laced up on the rear of the cover.



26. Adjust Car Seat Anchor Flaps

There are flaps covering all 4x Child Anchor slots. Un-Hook these flaps, feed them through the anchor slot and down, then attach the hook strip on the flap to the OEM cover to keep it secure.

NOTE: This will allow you to still easily access the anchors after the PRP Cover is installed.



27. Place the Cover on the Seat

Place the cover over the top of the seat. Tuck the cover around all the corners, and the rear/center of the seat.

Then flip the cover/seat over so that it is upside down on the table.



28. Attach the Front Flaps

There are two flaps on the front of the cover with a slot cut in it. Wrap those flaps over the two metal attachment brackets so they are secure.



29. Attach Draw Strings

There are 3x draw strings that are used to attach the cover to the rear foam on the rear passenger, center, and driver sides.

Then another 1x large draw string that runs across the entire rear of the seat.



30. Attach Driver/Passenger Draw Strings

Find the draw strings, and run both ends through the Car Seat Anchor Slots, so that the strings meet up in the rear. Feed the loose end of the string through the looped end string, pull it tight, and then tie it off in a knot. Do this on both Driver and Passenger sides.

NOTE: These strings only need to be moderately tight. Overtightening them will cause the cover to bind on the front.



31. Attach Center Draw Strings

Find the Draw String in the center, and run it through both seat belt slots. Connect them in the middle and tie them off.

Make sure that the metal bracket on the rear of the seat lines up with the square cut hole in the cover.



32. Attach Large Draw Strings

Find the Large Draw String in the rear of the cover. Connect the two strings and get them tight. (On this string you can use plyers to hold the string and get it as tight as you can to ensure best fitment). Tie it off in a knot.



33. Check Cover Fitment

Check the cover and make sure its fitting correctly. Push pull the cover around and adjust the cover and draw strings as needed. Once you are happy with it, you can cut off the excess draw sting.



34. Re-Install Bottom Cushion

Place the bottom cushion back into the vehicle. The Metal Bar on the middle-rear of the bench needs to attach to the black bracket on the floor.

Pull the seat belts through the slots in the bench so that they are accessible.



35. Re-Install Bottom Cushion (Cont.)

Once the cushion is connected in the back, then push down hard on the front of the bench so that the push clips connect on the front driver and passenger sides.



36. Install Headrest Covers

Grab one of the driver/passenger headrest covers and ensure its facing the correct way (logos go on front). Open up all the flaps on the bottom of the cover.

Slide the cover over the top of the headrest, and pull it down. You may also need to depress the foam and pull the cover to make it slide easier.



37. Attach Flaps Together

Once the cover is on, move it around and adjust the cover as needed so that it sits correctly on the headrest, and any logos are level.

Then wrap the sides flaps of the cover around the metal bars, and attach the hook & loop strips.



38. Finish Headrest Cover Install

Finally connect the front and rear flaps of the cover together. Adjust the cover as needed to get rid of any wrinkles or bulges.

Then re-install the headrests back onto the seat back.



39. Center Headrest Install

On the center headrest its easiest to place the cover over the front of the headrest first, then pull the cover back and wrap it around.



40. Center Headrest Install (Cont.)

Connect the side flaps of the cover first, then connect the front and back flaps.

Make sure the cover fits nicely, and adjust as needed.

Then re-install the headrest back onto the seat.



41. ... And You're All Done!

If you have any questions or experience issues, please contact your retail outlet first for help. However, the staff at PRP Seats is always happy to assist you.

1-800-317-6253.
customerservice@prpseats.com
Thank you! Drive safe!